PRODUCT DATA SHEET

Brackish Water Reverse Osmosis Systems (BWRO)



OVERVIEW

Microsoll's Brackish Water Reverse Osmosis (BWRO) plants are designed to treat water, with < 4,000 mg/L of dissolved solids (TDS) and < 10 mg/L of suspended solids (TSS), to achieve potable water quality. The standard treatment process involves pre filtration (auto backwashing multimedia filters and cartridge filters), anti-scalant dosing to prevent membrane scaling, RO desalination and auto flushing and CIP systems for membrane cleaning. Additional pre-RO and post-RO treatment steps may be added as required to suit feed water conditions and/or treated water quality requirements. The Waterland BWRO plants are available as skid mounted or containerised systems.

ADDITIONAL FLOW RATES AND CUSTOMISED SOLUTIONS ARE AVAILABLE. JUST ASK US.



STANDARD SPECIFICATIONS

Parameter	Units	BWRO-1	BWRO-2	BWRO-3	BWRO-4	BWRO-5	BWRO-6	BWRO-7	BWRO-8	BWRO-9	BWRO-10
Permeate Flow Rate	m³/h		0,5	0,75	1	2,5	5	7,5	10	15	20
Permeate Recovery Rate	%		50 - 70								
Permeate TDS	mg/L		< 100								
Raw Water TDS	mg/L		< 4,000								
Raw Water TSS	mg/L		< 10								
Raw Water Temperature	°C		15 ~ 30								
Ambient Design Temperature	°C		15 ~ 30								
RO Water Inlet Pressure	bar		3 - 4								
RO Unit High Pressure	bar		10 - 14								
RO Brine Discharge Pressure	bar		9 - 13								
Power Supply	-	AC 220-380~450 V, 3 Phase, 50/60 Hz									
No. Containers (Optional)	-	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'	1 x 20'

MEDIA FILTER

PUMP

CARTRIDGE

HP PUMP PERMEATE -REJECT ----

Equipment		BWRO-1	BWRO-2	BWRO-3	BWRO-4	BWRO-5	BWRO-6	BWRO-7	BWRO-8	BWRO-9	BWRO-10
Skid Mounted Plant & Equipment		✓	1	✓	1	1	✓	1	✓	1	1
Low Pressure Feed Pump		✓	✓	✓	1	✓	✓	1	✓	1	1
High Pressure RO	Std Efficiency	1	1	1	1	1	1	1	1	1	/
Pump (c/w ERD)	High Efficiency	-	0	0	0	0	0	0	0	0	0
	Multimedia	0	0	✓	1	1	✓	1	✓	1	1
Pre-filtration	Ultra Filtration	0	0	0	0	0	0	0	0	0	0
	Activated Carbon	✓	1	1	1	1	✓	1	✓	1	1
	Cartridge Filters	✓	1	✓	1	1	✓	1	✓	1	1
Anti Scalant Dosing System		✓	✓	✓	1	1	✓	1	✓	1	✓
Membrane CIP & Auto Flush System		0	0	0	0	0	✓	1	✓	1	1
PLC Control System with HMI		0	0	✓	1	1	✓	1	✓	1	✓
Container with Insulation & climated		0	0	0	0	0	0	0	0	0	0
Additional Post-RO Treatment		0	0	0	0	0	0	0	0	0	0
Premium Instrumentation Package		0	0	0	0	0	0	0	0	0	0
Permeate Distribution Pump Set		0	0	0	0	0	0	0	0	0	0

Instrumentation	Standard Package				
Pressure Gauges	✓				
Pressure Transmitters (4-20 mA)	0				
HP RO Pump Inlet Low Pressure Switch	✓				
Flow Gauges (Rotameters)	✓				
Flow Transmitters (4-20 mA)	0				
Conductivity Transmitter (4-20 mA)	✓				
Float Switches (Feed/Permeate, Chemical Dosing & CIP Tanks)	√				
Remote Monitoring & Control Capabilities	0				



